NSN 5910-00-837-3043

Quartz Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-837-3043 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.975 inches **Shaft Diameter:** 0.112 inches single shaft **Bushing Length:** 0.442 inches **Shaft Length:** 0.442 inches single shaft **Body Length:** 0.535 inches **Overall Diameter:** 0.313 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.280 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.275 inches **Quality Factor At 25 Deg Celsius:** 2000.0 **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.000 inch-ounces and 8.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 100.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 32 **Nonderated Operating Temp:** Between -55.0 degrees celsius and 150.0 degrees celsius **Thread Size:** 0.112 inches **Shaft Type:**

Round, slotted single shaft

NSN 5910-00-837-3043

Quartz Dielectric Variable Capacitor - Page 2 of 2



Capacitance Range In Picofarads:
+0.6/+5.0 single section
Nonderated Voltage Rating And Type:
750.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 shaft
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A096a0