

View Online at <https://aerobasegroup.com/nsn/5910-00-840-0603>

**Body Style:**

W/o mtg facilities terminal (s) on one surface/w/o mtg facilities terminal(s) on one surface/w/o mtg facilities terminal(s) on one surface/w/o mtg facilities terminal(s) on one surface

**Mil-std-1276 Wire Lead Type Designator:**

N-2n-2n-2n-2

**Reliability Indicator:**

Not established/not established/not established/not established

**Terminal Length:**

1.250 inches 1.250 inches 1.250 inches

**Body Length:**

0.300 inches 0.300 inches

**Body Width:**

0.300 inches 0.300 inches

**Body Height:**

0.100 inches 0.100 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.200 inches 0.200 inches

**Terminal Diameter:**

0.025 inches 0.025 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)/no common or grounded electrode(s)

**Insulation Resistance At Maximum Operating Temp:**

100.0 megohm-microfarads/100.0 megohm-microfarads

**Capacitance Value Per Section:**

22000.000 picofarads single section/22000.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-15.0/+15.0 without voltage applied single section/-15.0/+15.0 without voltage applied single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and -55.0 degrees celsius and 85.0 degrees celsius/85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc single section/200.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section/-10.00/+10.00 percent single section

**Case Material:**

Plastic/plastic

**Insulation Resistance At Reference Temp:**

1000.0 megohm-microfarads/1000.0 megohm-microfarads

**Dissipation Factor At Reference Temperature In Percent:**

2.5000/2.5000

**Precious Material And Location:**

Terminal surfaces gold/terminal surfaces gold

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0