

View Online at <https://aerobasegroup.com/nsn/5910-00-840-0603>

Body Style:

W/o mtg facilities terminal (s) on one surface/w/o mtg facilities terminal(s) on one surface/w/o mtg facilities terminal(s) on one surface/w/o mtg facilities terminal(s) on one surface

Mil-std-1276 Wire Lead Type Designator:

N-2n-2n-2n-2

Reliability Indicator:

Not established/not established/not established/not established

Terminal Length:

1.250 inches 1.250 inches 1.250 inches

Body Length:

0.300 inches 0.300 inches

Body Width:

0.300 inches 0.300 inches

Body Height:

0.100 inches 0.100 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.200 inches 0.200 inches

Terminal Diameter:

0.025 inches 0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)/no common or grounded electrode(s)

Insulation Resistance At Maximum Operating Temp:

100.0 megohm-microfarads/100.0 megohm-microfarads

Capacitance Value Per Section:

22000.000 picofarads single section/22000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section/-15.0/+15.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and -55.0 degrees celsius and 85.0 degrees celsius/85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section/200.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section/-10.00/+10.00 percent single section

Case Material:

Plastic/plastic

Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads/1000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

2.5000/2.5000

Precious Material And Location:

Terminal surfaces gold/terminal surfaces gold

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0