## NSN 5910-00-840-1348

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-840-1348

| Body Style:   |
|---|
| W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surface |
| Reliability Indicator:  |
| Not establishednot established  |
| Terminal Length:  |
| 1.250 inches  |
| Body Length:  |
| 0.300 inches  |
| Body Width:   |
| 0.300 inches  |
| Body Height:  |
| 0.100 inches  |
| Center To Center Distance Between Terminals Parallel To Length:                             |
| 0.200 inches  |
| Schematic Diagram Designator:   |
| No common or grounded electrode (s)   |
| Capacitance Value Per Section:  |
| 0.470 microfarads single section  |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change:                       |
| -30.0/+15.0 without voltage applied single section  |
| Nonderated Operating Temp:  |
| Between -55.0 degrees celsius and 125.0 degrees celsius                                     |
| Nonderated Continuous Voltage Rating And Type Per Section:                                  |
| 100.0 dc single section   |
| Tolerance Range Per Section:  |
| -10.00/+10.00 percent single section  |
| Case Material:  |
| Ceramic   |
| Insulation Resistance At Reference Temp:  |
| 20000.0 megohms   |
| Power Factor At Reference Tempurature In Percent:   |
| 2.500   |
| Terminal Surface Treatment:   |
| Solder  |
| Terminal Type And Quantity:   |
| 2 uninsulated wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5910-00-840-1348

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0