NSN 5910-00-840-1702

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-840-1702 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Body Diameter:** 1.250 inches **Body Length:** 2.562 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil Impedance At Minimum Operating Tempurature In Ohms: 16.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 470.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 15.0000 Dc Leakage At Reference Temp: 230.000 microamperes **Terminal Surface Treatment:** Nickel **Test Data Document:** 81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 standard tube base

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5910-00-840-1702

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0