## NSN 5910-00-840-2631

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-840-2631

| Body Style:   |
|---|
| W/o mtg facilities, terminal (s) on one end   |
| Reliability Indicator:  |
| Not established   |
| Body Diameter:  |
| 1.250 inches  |
| Body Length:  |
| 3.046 inches  |
| Schematic Diagram Designator:   |
| No common or grounded electrode (s)   |
| Anode Type:   |
| Plain foil  |
| Impedance At Minimum Operating Tempurature In Ohms:   |
| 65.0  |
| Electrical Polarization:  |
| Polarized   |
| Capacitance Value Per Section:  |
| 68.000 microfarads single section   |
| Nonderated Operating Temp:  |
| Between -40.0 degrees celsius and 85.0 degrees celsius  |
| Nonderated Continuous Voltage Rating And Type Per Section:  |
| 200.0 dc single section   |
| Tolerance Range Per Section:  |
| -10.00/+50.00 percent single section  |
| Case Material:  |
| Metal   |
| Capacitive Electrode Material:  |
| Aluminum  |
| Dissipation Factor At Reference Tempurature In Percent:   |
| 12.0000   |
| Dc Leakage At Reference Temp:   |
| 150.000 microamperes  |
| Terminal Surface Treatment:   |
| Nickel  |
| Test Data Document:   |
| 81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Terminal Type And Quantity:   |
| 2 standard tube base  |
| Shelf Life:   |

--

N/a

**Unit Of Measure:** 

## NSN 5910-00-840-2631

Electrolytic Fixed Capacitor - Page 2 of 2



| _  |     |         |     |   |  |
|----|-----|---------|-----|---|--|
| 11 | em) | <br>tor | 172 | n |  |
|    |     |         |     |   |  |

No

Fiig:

A010b0