## NSN 5910-00-841-8818

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-841-8818

<b>D</b> -	٠. د	C4	٠
DU	uv	Stv	ıe:

W/o mtg facilities, radial terminalsw/o mtg facilities, radial ter

## **Reliability Indicator:**

Not establishednot establishednot established

## **Terminal Length:**

1.500 inches 1.500 inches 1.500 inches

**Body Diameter:** 

0.312 inches

**Body Length:** 

0.550 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

0.250 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

27.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-30.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

**Tolerance Range Per Section:** 

-2.00/+2.00 percent single section

**Case Material:** 

Plastic

Insulation Resistance At Reference Temp:

7500.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.1500

**Terminal Surface Treatment:** 

Solder

**Precious Material And Location:** 

Part of element silver

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-00-841-8818

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A010b0