

View Online at <https://aerobasegroup.com/nsn/5910-00-843-4545>

### Body Style:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

### Reliability Indicator:

Not establishednot establishednot established

### Terminal Length:

1.250 inches 1.250 inches 1.250 inches

### Body Diameter:

0.225 inches

### Body Length:

0.540 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

### Capacitance Value Per Section:

5.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-150.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

### Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-60.0/+60.0 single section

### Tolerance Range Per Section:

-0.25/+0.25 picofarads single section

### Case Material:

Ceramic

### Insulation Resistance At Reference Temp:

50000.0 megohms

### Quality Factor At Reference Temp:

490.0000

### Terminal Surface Treatment:

Solder

### Test Data Document:

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

2 uninsulated wire lead

### Shelf Life:

N/a

### Unit Of Measure:

--

**Demilitarization:**

No

**Fiig:**

A010b0