NSN 5910-00-846-2529

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-846-2529 **Body Style:** W/mtg bracket, axial terminals **Reliability Indicator:** Not established **Unable To Decode:** Unable to decode and unable to decode **Terminal Length:** 2.438 inches **Body Diameter:** 0.703 inches **Body Length:** Between 1.937 inches and 2.063 inches **Terminal Diameter:** 0.032 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd ter minal **Mounting Facility Type And Quantity:** 2 unthreaded mounting holes **Capacitance Value Per Section:** 2.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -15.00/+15.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 500.0 megohms **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life:

N/a

Unit Of Measure:

NSN 5910-00-846-2529

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	2 †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A010b0