

View Online at <https://aerobasegroup.com/nsn/5910-00-846-8659>

**Body Style:**

W/thd bushing mtg, terminals on opposite endw/thd bushing mtg, terminals on opposite endw/thd bushing mtg, terminals on opposite end

**Reliability Indicator:**

Not establishednot establishednot established

**Width Across Flats:**

0.312 inches 0.312 inches 0.312 inches

**Terminal Length:**

0.406 inches 0.406 inches 0.406 inches

**Body Length:**

0.750 inches

**Terminal Diameter:**

0.025 inches

**Schematic Diagram Designator:**

Feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unf

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Mounting hardware

**Capacitance Value Per Section:**

5000.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-56.0/+22.0 without voltage applied single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.216 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Metal

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0