NSN 5910-00-851-7794

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-851-7794
Body Style:
W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals
Reliability Indicator:
Not establishednot established
Terminal Length:
1.500 inches
Body Diameter:
0.563 inches
Body Length:
0.156 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
Ticonderoga class cg (47); missile, air intercept, sidewinder (aim-9); missile, all-weather antiship, harpoon (agm-84); los angeles class
ssn (688); sturgeon class ssn (637); radar, series an/sps-4 (v); teletype, model 28; support equipment, b-1 aircraft; integrated launch &
recovery tv surveillance sys (ilarts)
Capacitance Value Per Section:
10000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
1000.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-60.0/+60.0 single section
Criticality Code Justification:
Feat
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Plastic
Terminal Surface Treatment:
Solder
Special Features:

N/a

Unit Of Measure:

Shelf Life:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

--

NSN 5910-00-851-7794

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0