## NSN 5910-00-852-1266



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-852-1266 **Body Style:** W/thd bushing mtg, terminal (s) on one end **Reliability Indicator:** Not established **Terminal Length:** 0.625 inches **Body Diameter:** 0.875 inches **Body Length:** 0.500 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Electrical Polarization:** Polarized **Mounting Facility Screw Thread Series Designator: Mounting Facility Type And Quantity:** 1 threaded bushing **Features Provided:** Mounting hardware and hermetically sealed case **Capacitance Value Per Section:** 120.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 120.0 degrees celsius **Thread Size:** 0.500 inches Dc Leakage At Maximum Operating Temp: 346.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 18.0 dc single section **Tolerance Range Per Section:** -15.00/+75.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Tantalum Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 

Shelf Life:

N/a

1 tab, solder lug

## NSN 5910-00-852-1266

Electrolytic Fixed Capacitor - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A010b0