

View Online at <https://aerobasegroup.com/nsn/5910-00-852-7098>

**Body Style:**

W/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:**

Not established/not established

**Width Across Flats:**

0.312 inches 0.312 inches

**Body Length:**

0.750 inches

**Schematic Diagram Designator:**

Feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unf

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Capacitance Value Per Section:**

47.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-25.0/+15.0 with rated voltage applied single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.250 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

1000.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

20000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

1.500

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 wire hook/loop

**Specification Data:**

81349-mil-c-11015/13 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0