Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-853-2199

# **Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

0.516 inches

## **Body Length:**

2.062 inches

#### **Body Width:**

1.500 inches

#### **Body Height:**

### 2.062 inches

## Center To Center Distance Between Terminals Parallel To Length:

1.250 inches

### **Unthreaded Mounting Hole Diameter:**

## 0.188 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.375 inches

# Schematic Diagram Designator:

No common or grounded electrode (s)

# Mounting Facility Type And Quantity:

2 unthreaded mounting holes

# **Features Provided:**

Mounting hardware and hermetically sealed case

# Insulation Resistance At Maximum Operating Temp:

500.0 megohms

### **Capacitance Value Per Section:**

10.000 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Metal

**Dielectric Material:** 

Plastic polyethylene terephthalate

# **Terminal Type And Quantity:**

2 tab, solder lug

### Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0