## NSN 5910-00-853-5752

Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-853-5752

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.420 inches
Body Width:
0.290 inches
Body Height:
0.170 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Capacitance Value Per Section:
1000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Detween -00.0 degrees delaids and 00.0 degrees delaids
Tolerance Range Per Section:
Tolerance Range Per Section:
Tolerance Range Per Section: -10.00/+10.00 percent single section
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dielectric Material:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dielectric Material: Plastic polyethylene terephthalate
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dielectric Material: Plastic polyethylene terephthalate  Special Features:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dielectric Material: Plastic polyethylene terephthalate  Special Features: Tin plated copper clad terminal surface
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dielectric Material: Plastic polyethylene terephthalate  Special Features: Tin plated copper clad terminal surface  Terminal Type And Quantity:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dielectric Material: Plastic polyethylene terephthalate  Special Features: Tin plated copper clad terminal surface  Terminal Type And Quantity: 2 uninsulated wire lead
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dielectric Material: Plastic polyethylene terephthalate  Special Features: Tin plated copper clad terminal surface  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dielectric Material: Plastic polyethylene terephthalate  Special Features: Tin plated copper clad terminal surface  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dielectric Material: Plastic polyethylene terephthalate  Special Features: Tin plated copper clad terminal surface  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dielectric Material: Plastic polyethylene terephthalate  Special Features: Tin plated copper clad terminal surface  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:

A010b0