

View Online at <https://aerobasegroup.com/nsn/5910-00-853-8297>

Thread Class:

2a

Body Style:

Plate-meshing

Overall Length:

1.532 inches

Bushing Diameter:

0.250 inches

Overall Height:

0.906 inches

Overall Width:

0.781 inches

Shaft Diameter:

0.188 inches single shaft

Bushing Length:

0.250 inches

Shaft Length:

0.250 inches single shaft

Body Length:

0.938 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

30.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Quality Factor At 25 Deg Celsius:

1000.0

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Uninclosed

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Rotation:

180.0 degrees clockwise

Adjustment Device Torque:

Between 5.000 inch-ounces and 15.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

50.0 gigohms

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.250 inches

Shaft Type:

Round, slotted single shaft

Capacitance Range In Picofarads:

+3.4/+32.0 single section

Nonderated Voltage Rating And Type:

600.0 ac peak single section

Adjustment Device Drive Type And Quantity:

1 shaft

Special Features:

Alternate post terminals for one solder lug

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0