

View Online at <https://aerobasegroup.com/nsn/5910-00-853-8298>

Thread Class:

2a

Body Style:

Plate-meshing

Overall Length:

1.641 inches

Bushing Diameter:

0.250 inches

Overall Height:

0.906 inches

Overall Width:

0.781 inches

Shaft Diameter:

0.188 inches single shaft

Bushing Length:

0.250 inches

Shaft Length:

0.250 inches single shaft

Body Length:

1.141 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

30.0 single section

Quality Factor At 25 Deg Celsius:

1000.0

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Uninclosed

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Rotation:

180.0 degrees clockwise

Adjustment Device Torque:

Between 5.000 inch-ounces and 15.000 inch-ounces

Bushing Shape:

Round w/double flat

Insulation Dc Resistance At 25 Deg Celsius:

50.0 gigohms

Bushing Width:

0.188 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 65.0 degrees celsius

Thread Size:

0.250 inches

Shaft Type:

Round, slotted single shaft

Capacitance Range In Picofarads:

+3.7/+45.0 single section

Nonderated Voltage Rating And Type:

600.0 ac rms single section

Adjustment Device Drive Type And Quantity:

1 shaft

Terminal Type And Quantity:

2 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0