## NSN 5910-00-854-9266

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-854-9266

| view Offiline at https://aerobasegroup.com/nish/5510-00-054-5200 |
|--|
| Body Style:  |
| W/o mtg facilities, terminals on opposite surfaces               |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| 1.625 inches   |
| Body Length:   |
| Between 0.563 inches and 0.687 inches                            |
| Body Width:  |
| Between 0.350 inches and 0.450 inches                            |
| Body Height:   |
| Between 0.450 inches and 0.550 inches                            |
| Terminal Diameter:   |
| 0.025 inches   |
| Schematic Diagram Designator:                                    |
| No common or grounded electrode (s)                              |
| Capacitance Value Per Section:                                   |
| 0.220 microfarads single section                                 |
| Nonderated Operating Temp:                                       |
| Between -55.0 degrees celsius and 100.0 degrees celsius          |
| Nonderated Continuous Voltage Rating And Type Per Section:       |
| 400.0 dc single section  |
| Tolerance Range Per Section:                                     |
| -20.00/+20.00 percent single section                             |
| Case Material:   |
| Metal  |
| Insulation Resistance At Reference Temp:                         |
| 50000.0 megohm-microfarads                                       |
| Dissipation Factor At Reference Tempurature In Percent:          |
| 1.500  |
| Terminal Surface Treatment:                                      |
| Solder   |
| Case Insulation Material:  |
| Plastic  |
| Terminal Type And Quantity:                                      |
| 2 uninsulated wire lead  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

No

Demilitarization:

## NSN 5910-00-854-9266

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0