## NSN 5910-00-855-2571

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-855-2571

Body	Stv	le:
DOUN	/ <b>ULV</b>	IC.

W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s)

## **Reliability Indicator:**

Not establishednot established

**Terminal Length:** 

1.250 inches 1.250 inches 1.250 inches

**Body Length:** 

0.190 inches

**Body Width:** 

0.190 inches

**Body Height:** 

0.090 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.185 inches and 0.215 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

10000.0 megohms

**Capacitance Value Per Section:** 

100.000 picofarads single section

**Voltage Tempurature Limits Per Section In Percent Capacitance Change:** 

-10.0/+10.0 with rated voltage applied single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 150.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Ceramic

Insulation Resistance At Reference Temp:

100000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

1.5000

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

**Reference Number Differentiating Characteristics:** 

Qual cont for polaris

Shelf Life:

N/a

## NSN 5910-00-855-2571

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0