NSN 5910-00-855-2734

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-855-2734 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.281 inches **Body Length:** 0.938 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms: Electrical Polarization:** Nonpolarized **Capacitance Value Per Section:** 3.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 30.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Power Factor At Reference Tempurature In Percent:** 10.0000 **Equivalent Series Resistance At Reference Tempurature In Ohms:** 135.00 Dc Leakage At Reference Temp: 5.300 microamperes **Terminal Surface Treatment:** Solder

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-855-2734

Electrolytic Fixed Capacitor - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0