NSN 5910-00-855-5851

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



| raper-plastic Dielectric Metallized Fixed Capacitor - rage 1 of 2 | |
|--|--|
| View Online at https://aerobasegroup.com/nsn/5910-00-855-5851 | |
| Body Style: | |
| W/mtg tabs/flanges, terminal (s) on one surface | |
| Reliability Indicator: | |
| Not established | |
| Terminal Length: | |
| 0.750 inches | |
| Body Length: | |
| 2.000 inches | |
| Body Width: | |
| 2.000 inches | |
| Body Height: | |
| 1.250 inches | |
| Center To Center Distance Between Terminals Parallel To Length: | |
| 1.063 inches | |
| Unthreaded Mounting Hole Diameter: | |
| 0.188 inches | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: | |
| 2.375 inches | |
| Schematic Diagram Designator: | |
| No common or grounded electrode (s) | |
| Mounting Facility Type And Quantity: | |
| 2 unthreaded mounting holes | |
| Features Provided: | |
| Hermetically sealed case | |
| Capacitance Value Per Section: | |
| 3.000 microfarads single section | |
| Nonderated Operating Temp: | |
| Potwoon, 55.0 dogroop coloius and 125.0 dogroop coloius | |

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

Power Factor At Reference Tempurature In Percent:

1.0000

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

NSN 5910-00-855-5851

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| | | • - | | | | | | |
|---|-----|-----|----|-----|----|----|----|----|
| | In | | Of | RЛ | മാ | CI | ır | Δ. |
| L | ,,, | | | IVI | ca | | | |

--

Demilitarization:

No

Fiig:

A010b0