## NSN 5910-00-855-6688



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-855-6688 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Terminal Length:** 1.500 inches **Body Diameter:** 0.185 inches **Body Length:** 0.474 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 3.300 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 65.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Tantalum** Dc Leakage At Reference Temp: 2.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

81349-mil-c-26655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5910-00-855-6688

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0