

View Online at <https://aerobasegroup.com/nsn/5910-00-856-1602>

**Body Style:**

W/thd mtg hole/stud, terminal (s) on one endw/thd mtg hole/stud, terminal(s) on one endw/thd mtg hole/stud, terminal(s) on one end

**Reliability Indicator:**

Not establishednot establishednot established

**Width Across Flats:**

0.250 inches 0.250 inches 0.250 inches

**Terminal Length:**

0.250 inches 0.250 inches 0.250 inches

**Body Diameter:**

0.469 inches

**Body Length:**

0.469 inches

**Terminal Diameter:**

0.051 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case

**Mounting Facility Screw Thread Series Designator:**

Unf

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Capacitance Value Per Section:**

1000.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.216 inches

**Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:**

0.0 single section

**Nonderated Continuous Voltage Rating And Type Per Section:**

500.0 dc single section

**Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:**

-15.0/+15.0 single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

7500.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

1.5000

**Power Factor At Reference Temperature In Percent:**

25.0000

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

1 wire hook/loop

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0