

View Online at <https://aerobasegroup.com/nsn/5910-00-856-1602>

Body Style:

W/thd mtg hole/stud, terminal (s) on one endw/thd mtg hole/stud, terminal(s) on one endw/thd mtg hole/stud, terminal(s) on one end

Reliability Indicator:

Not establishednot establishednot established

Width Across Flats:

0.250 inches 0.250 inches 0.250 inches

Terminal Length:

0.250 inches 0.250 inches 0.250 inches

Body Diameter:

0.469 inches

Body Length:

0.469 inches

Terminal Diameter:

0.051 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

1000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.216 inches

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-15.0/+15.0 single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

7500.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.5000

Power Factor At Reference Tempurature In Percent:

25.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

1 wire hook/loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0