

View Online at <https://aerobasegroup.com/nsn/5910-00-864-9311>

Body Style:

W/thd bushing mtg, terminals on opposite endw/thd bushing mtg, terminals on opposite end

Reliability Indicator:

Not establishednot established

Width Across Flats:

0.250 inches 0.250 inches

Terminal Length:

0.219 inches 0.219 inches

Body Length:

0.171 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded mounting studs

Insulation Resistance At Maximum Operating Temp:

3000.0 megohms

Capacitance Value Per Section:

100.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.099 inches

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

40000.0 megohms

Quality Factor At Reference Temp:

20.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

1 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0