

View Online at <https://aerobasegroup.com/nsn/5910-00-864-9311>

**Body Style:**

W/thd bushing mtg, terminals on opposite endw/thd bushing mtg, terminals on opposite end

**Reliability Indicator:**

Not establishednot established

**Width Across Flats:**

0.250 inches 0.250 inches

**Terminal Length:**

0.219 inches 0.219 inches

**Body Length:**

0.171 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

1 threaded mounting studs

**Insulation Resistance At Maximum Operating Temp:**

3000.0 megohms

**Capacitance Value Per Section:**

100.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.099 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

500.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

40000.0 megohms

**Quality Factor At Reference Temp:**

20.0000

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

1 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0