

View Online at <https://aerobasegroup.com/nsn/5910-00-864-9513>

Body Style:

W/thd mtg bushing, terminals on opposite endsw/thd mtg bushing, terminals on opposite endsw/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not establishednot establishednot established

Width Across Flats:

0.312 inches 0.312 inches 0.312 inches

Terminal Length:

0.235 inches 0.235 inches 0.235 inches

Body Length:

0.827 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unef

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

470.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.216 inches

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

2.0000

Quality Factor At Reference Temp:

50.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0