NSN 5910-00-866-4105

Body Style:

N/a

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-866-4105

| W/thd mtg hole/stud, terminal (s) on one end |
|--|
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.625 inches |
| Body Diameter: |
| 0.562 inches |
| Body Length: |
| 1.312 inches |
| Continuous Current Rating In Amps: |
| 1.0 |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Mounting Facility Type And Quantity: |
| 1 threaded mounting studs |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 0.220 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Thread Size: |
| 0.138 inches |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 400.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Metal |
| Power Factor At Reference Tempurature In Percent: |
| 1.0000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 1 uninsulated wire lead |
| Shelf Life: |

NSN 5910-00-866-4105

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| | | • - | | | | | |
|---|-----|------|------|------|----|-----|----|
| ш | ın | 18 1 | r 1+ | Me | 20 | ıır | Δ. |
| u | ,,, | IL | v. | IAIC | as | uı | ┖. |

--

Demilitarization:

No

Fiig:

A010b0