Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-873-2734

### **Body Style:**

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

#### **Reliability Indicator:**

Not established

## **Terminal Length:**

0.389 inches

### **Body Length:**

2.003 inches

#### **Body Width:**

1.500 inches

#### **Body Height:**

#### 2.003 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.041 inches

#### Schematic Diagram Designator:

### No common or grounded electrode (s)

## Mounting Facility Screw Thread Series Designator:

Unc

### Mounting Facility Type And Quantity:

2 threaded mounting studs

## **Capacitance Value Per Section:**

10.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

#### **Thread Size:**

0.134 inches

### Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

## Insulation Resistance At Reference Temp:

10000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.500

## **Terminal Surface Treatment:**

Solder

## **Terminal Type And Quantity:**

2 tab, solder lug

#### Shelf Life:

N/a

Paper Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0