## NSN 5910-00-879-9827

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-879-9827 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Terminal Length:** 1.500 inches **Body Diameter:** 0.289 inches **Body Length:** 0.686 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 33.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 65.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum** Dc Leakage At Reference Temp: 13.000 microamperes **Terminal Surface Treatment:** Solder **Test Data Document:** 81349-mil-c-26655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5910-00-879-9827

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0