NSN 5910-00-880-7235

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-880-7235

Body Style: W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.312 inches **Body Length:** 0.945 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Etched foil **Impedance At Minimum Operating Tempurature In Ohms: Electrical Polarization:** Nonpolarized **Capacitance Value Per Section:** 6.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 6.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Power Factor At Reference Tempurature In Percent:** 10.0000 Dc Leakage At Reference Temp: 2.000 microamperes **Terminal Surface Treatment:** Solder **Test Data Document:** 81349-mil-c-3965 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-880-7235

Electrolytic Fixed Capacitor - Page 2 of 2



Shelf	LIIE.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0