## NSN 5910-00-882-8580

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-882-8580 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 0.500 inches **Body Width:** 0.280 inches **Body Height:** 0.125 inches **Center To Center Distance Between Terminals Parallel To Length:** Between 0.395 inches and 0.405 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 1000.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Terminal Surface Treatment:** Solder **Test Data Document:** 03640-6096381 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5910-00-882-8580

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0