NSN 5910-00-882-8710

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-882-8710

Body Style:							
W/mtg tabs/flanges, terminal (s) on one surface							
Reliability Indicator:							
Not established							
Terminal Length:							
0.312 inches							
Body Length:							
1.812 inches							
Body Width:							
1.000 inches							
Body Height:							
0.750 inches							
Center To Center Distance Between Terminals Parallel To Length:							
1.062 inches							
Unthreaded Mounting Hole Diameter:							
0.188 inches							
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:							
2.125 inches							
Schematic Diagram Designator:							
No common or grounded electrode (s)							
Mounting Facility Type And Quantity:							
2 unthreaded mounting holes							
Features Provided:							
-							
Features Provided:							
Features Provided: Hermetically sealed case							
Features Provided: Hermetically sealed case Capacitance Value Per Section:							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section Nonderated Operating Temp:							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 150.0 degrees celsius							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section:							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 10000.0 megohms							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp:							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 10000.0 megohms							
Features Provided: Hermetically sealed case Capacitance Value Per Section: 2.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 10000.0 megohms Terminal Surface Treatment:							

N/a

Shelf Life:

NSN 5910-00-882-8710

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0