Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-883-0087

#### **Body Style:**

W/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not established

## **Terminal Length:**

2.500 inches

#### **Body Diameter:**

0.750 inches

#### **Body Length:**

2.125 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Plain foil

#### **Electrical Polarization:**

Polarized

## **Capacitance Value Per Section:**

1000.000 microfarads single section

### Nonderated Operating Temp:

Between -20.0 degrees celsius and 85.0 degrees celsius

### Dc Leakage At Maximum Operating Temp:

50.0 milliamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+75.00 percent single section

#### **Case Material:**

Metal

**Capacitive Electrode Material:** 

Aluminum

# Dissipation Factor At Reference Tempurature In Percent:

60.0000

# Dc Leakage At Reference Temp:

6.000 microamperes

# **Terminal Surface Treatment:**

Solder

# Case Insulation Material:

Plastic

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0