Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-883-1270

Body Style:

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

Reliability Indicator:

Not established

Body Length:

4.562 inches

Body Width:

3.750 inches

Body Height:

5.688 inches

Center To Center Distance Between Terminals Parallel To Length:

2.250 inches

Terminal Diameter:

0.781 inches

Terminal Height From Body:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.250 inches

Schematic Diagram Designator:

One terminal common to each section

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.625 inches

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

4 threaded mounting studs

Section Quantity:

2

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

50.0 megohms

Capacitance Value Per Section:

0.100 microfarads all sections

Nonderated Operating Temp:

Between 0.0 degrees celsius and 90.0 degrees celsius

Thread Size:

0.164 inches

Nonderated Continuous Voltage Rating And Type Per Section:

17500.0 dc all sections

Tolerance Range Per Section:

-10.00 to 10.00 percent all sections

NSN 5910-00-883-1270

Paper Dielectric Fixed Capacitor - Page 2 of 2



Case Material:

Metal

Insulation Resistance At Reference Temp:

5000.0 megohms

Power Factor At Reference Tempurature In Percent:

1.000

Terminal Type And Quantity:

3 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0