NSN 5910-00-883-1341

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-883-1341
Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Body Diameter:
0.681 inches
Body Length:
1.312 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Impedance At Minimum Operating Tempurature In Ohms:
1000.0
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
2.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
75.0 milliamperes
Nonderated Continuous Voltage Rating And Type Per Section:
340.0 dc single section
Tolerance Range Per Section:
-15.00/+50.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Equivalent Series Resistance At Reference Tempurature In Ohms:
40.00
Dc Leakage At Reference Temp:
15.000 microamperes
Terminal Surface Treatment:
Solder
Test Data Document:
18876-9174882-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

2 tab, solder lug

Terminal Type And Quantity:

NSN 5910-00-883-1341

Electrolytic Fixed Capacitor - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0