NSN 5910-00-883-1342

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-883-1342

Body Style: W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Body Diameter:** 0.681 inches **Body Length:** 1.781 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid Impedance At Minimum Operating Tempurature In Ohms: 600.0 **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 4.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 150.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 340.0 dc single section **Tolerance Range Per Section:** -15.00/+50.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Equivalent Series Resistance At Reference Tempurature In Ohms:** 20.00 Dc Leakage At Reference Temp: 30.000 microamperes **Terminal Surface Treatment:** Solder **Test Data Document:** 18876-9174882-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

2 tab, solder lug

Terminal Type And Quantity:

NSN 5910-00-883-1342

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0