## NSN 5910-00-888-5649

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-888-5649 **Body Style:** W/thd bushing mtg, terminal (s) on one end Reliability Indicator: Not established **Body Diameter:** 1.016 inches **Body Length:** 1.844 inches **Schematic Diagram Designator:** Electrod (s) grounded to case **Mounting Facility Screw Thread Series Designator:** Unef **Mounting Facility Type And Quantity:** 1 threaded bushing **Features Provided:** Mounting hardware and hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 40.0 megohm-microfarads **Capacitance Value Per Section:** 1.500 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.500 inches Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 2000.0 megohm-microfarads **Power Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

1 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5910-00-888-5649

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	tariz	

No

Fiig:

A010b0