

View Online at <https://aerobasegroup.com/nsn/5910-00-889-2431>

Thread Class:

Any acceptable

Body Style:

Piston

Overall Length:

0.806 inches

Bushing Diameter:

0.250 inches

Bushing Length:

0.250 inches

Body Length:

0.656 inches

Overall Diameter:

0.312 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

50.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Center To Center Distance Between Terminals Parallel To Length:

Any acceptable

Quality Factor At 25 Deg Celsius:

500.0

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encased

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Bushing Shape:

Round w/flat

Insulation Dc Resistance At 25 Deg Celsius:

1.0 gigohms

Bushing Width:

0.210 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.250 inches

Capacitance Range In Picofarads:

+0.8/+8.5 single section

Nonderated Voltage Rating And Type:

750.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Test Data Document:

13499-922-3035-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0