

View Online at <https://aerobasegroup.com/nsn/5910-00-889-2431>

**Thread Class:**

Any acceptable

**Body Style:**

Piston

**Overall Length:**

0.806 inches

**Bushing Diameter:**

0.250 inches

**Bushing Length:**

0.250 inches

**Body Length:**

0.656 inches

**Overall Diameter:**

0.312 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

50.0 single section

**Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:**

-50.0/+50.0 single section

**Center To Center Distance Between Terminals Parallel To Length:**

Any acceptable

**Quality Factor At 25 Deg Celsius:**

500.0

**Mounting Facility Screw Thread Series Designator:**

Unef

**Inclosure Type:**

Encased

**Adjustment Device Torque:**

Between 1.000 inch-ounces and 10.000 inch-ounces

**Bushing Shape:**

Round w/flat

**Insulation Dc Resistance At 25 Deg Celsius:**

1.0 gigohms

**Bushing Width:**

0.210 inches

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.250 inches

**Capacitance Range In Picofarads:**

+0.8/+8.5 single section

**Nonderated Voltage Rating And Type:**

750.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Test Data Document:**

13499-922-3035-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A096a0