NSN 5910-00-889-4385

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-889-4385

Body Style:

W/thd bushing mtg, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

0.296 inches

Body Diameter:

0.400 inches

Body Length:

1.062 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Internal Electrical Connection Type:

Extended foil

Mounting Facility Screw Thread Series Designator:

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

40000.0 megohm-microfarads

Capacitance Value Per Section:

10000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.312 inches

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-120.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

250000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

0.1000

NSN 5910-00-889-4385

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polystyrene
Terminal Type And Quantity:
1 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fila:

A010b0