NSN 5910-00-889-4669

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-889-4669 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 0.143 inches **Body Length:** 0.330 inches **Body Width:** 0.318 inches **Body Height:** 0.180 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.195 inches and 0.205 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Insulation Resistance At Maximum Operating Temp:** 1000.0 megohm-microfarads **Capacitance Value Per Section:** 680.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 10000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.3200 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyethylene terephthalate **Terminal Type And Quantity:** 2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-00-889-4669

Plastic Dielectric Fixed Capacitor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A010b0