Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-889-4679

# Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.143 inches

- Body Length:
- 0.330 inches

**Body Width:** 

0.318 inches

**Body Height:** 

0.180 inches

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.195 inches and 0.205 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

# Internal Electrical Connection Type:

Extended foil

#### Insulation Resistance At Maximum Operating Temp:

1000.0 megohm-microfarads

## Capacitance Value Per Section:

4700.000 picofarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

## **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

10000.0 megohm-microfarads

## **Dissipation Factor At Reference Tempurature In Percent:**

0.3200

## **Terminal Surface Treatment:**

Solder

**Dielectric Material:** 

Plastic polyethylene terephthalate

## **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0