## NSN 5910-00-889-4756

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-889-4756 **Thread Class:** 2a **Body Style:** Piston **Bushing Diameter:** 0.094 inches **Bushing Length:** 0.250 inches **Body Length:** 0.780 inches **Overall Diameter:** 0.156 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 25.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Terminal Diameter:** 0.032 inches **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.500 inch-ounces and 5.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.190 inches Capacitance Range In Picofarads: +1.0/+14.0 single section **Nonderated Voltage Rating And Type:** 750.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Terminal Type And Quantity:** 

1 wire lead

## NSN 5910-00-889-4756

Glass Dielectric Variable Capacitor - Page 2 of 2



| Shelf | Life: |
|-------|-------|
| N/a   |       |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0