## NSN 5910-00-890-4300

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-890-4300

<b>D</b> -	٠. د	C4	٠
DU	uv	Stv	ıe:

W/thd mtg hole/stud, terminal (s) on one endw/thd mtg hole/stud, terminal(s) on one endw/thd mtg hole/stud, terminal(s) on one end

**Reliability Indicator:** 

Not establishednot established

Width Across Flats:

0.875 inches 0.875 inches 0.875 inches

**Terminal Length:** 

0.750 inches 0.750 inches 0.750 inches

**Body Diameter:** 

0.375 inches

**Body Length:** 

1.000 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

Electrod (s) grounded to case

**Mounting Facility Screw Thread Series Designator:** 

Unc

**Mounting Facility Type And Quantity:** 

1 threaded mounting studs

**Capacitance Value Per Section:** 

2200.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:** 

0.112 inches

Nonderated Continuous Voltage Rating And Type Per Section:

350.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Metal

**Insulation Resistance At Reference Temp:** 

7500.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

3.0000

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

1 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-00-890-4300

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0