

View Online at https://aerobasegroup.com/nsn/5910-00-892-7457

# Body Style:

W/thd bushing mtg, terminals on opposite ends

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.296 inches

#### **Body Diameter:**

1.000 inches

**Body Length:** 

2.562 inches

## **Continuous Current Rating In Amps:**

1.0

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Mounting Facility Screw Thread Series Designator:

Unf

## Mounting Facility Type And Quantity:

1 threaded bushing

#### **Features Provided:**

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

1.0 megohm-microfarads

## Capacitance Value Per Section:

12.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### **Thread Size:**

0.312 inches

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

#### Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

## Power Factor At Reference Tempurature In Percent:

1.5000

# **Terminal Surface Treatment:**

Solder

## **Terminal Type And Quantity:**

2 tab, solder lug

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0