NSN 5910-00-892-7728

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-892-7728 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Diameter:** 0.391 inches **Body Length:** 0.828 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 50.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 60.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -15.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Tantalum Equivalent Series Resistance At Reference Tempurature In Ohms:** Dc Leakage At Reference Temp: 2.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:** Plastic **Terminal Type And Quantity:** 2 uninsulated wire lead

N/a

Shelf Life:

NSN 5910-00-892-7728

Electrolytic Fixed Capacitor - Page 2 of 2



| U | n | it | Of | Μe | eas | ur | e: |
|---|---|----|----|----|-----|----|----|
| | | | | | | | |

--

Demilitarization:

No

Fiig:

A010b0