Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-892-7830

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

# **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.135 inches

#### **Body Length:**

0.422 inches

## Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

## Anode Type:

Solid

## **Electrical Polarization:**

Polarized

## **Features Provided:**

Hermetically sealed case

## **Capacitance Value Per Section:**

2.200 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 65.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

**Capacitive Electrode Material:** 

Tantalum

**Terminal Surface Treatment:** 

Solder

# **Case Insulation Material:**

Plastic

# Test Data Document:

81349-milc26655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a

# NSN 5910-00-892-7830

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0