

View Online at <https://aerobasegroup.com/nsn/5910-00-895-7709>

**Thread Class:**

2a

**Body Style:**

Piston

**Terminal Length:**

0.500 inches

**Bushing Diameter:**

Between 0.191 inches and 0.195 inches

**Shaft Diameter:**

0.190 inches single shaft

**Bushing Length:**

0.406 inches

**Shaft Length:**

0.281 inches single shaft

**Body Length:**

Between 0.438 inches and 0.500 inches

**Overall Diameter:**

0.313 inches

**Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:**

-150.0/+150.0 single section

**Quality Factor At 25 Deg Celsius:**

500.0

**Fragility Factor:**

Moderately rugged

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Encased

**Adjustment Device Torque:**

Between 1.000 inch-ounces and 10.000 inch-ounces

**Bushing Shape:**

Round w/flat

**Insulation Dc Resistance At 25 Deg Celsius:**

1000000.0 megohms

**Bushing Width:**

Between 0.171 inches and 0.175 inches

**Mounting Facility Type And Quantity:**

1 locking bushing

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.190 inches

**Shaft Type:**

Round, slotted single shaft

**Capacitance Range In Picofarads:**

+1.0/+14.0 single section

**Nonderated Voltage Rating And Type:**

1000.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:**

1 hex nut w/screwdriver slot

**Material:**

Ceramic capacitive electrode

**Terminal Type And Quantity:**

1 turret and 1 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0