NSN 5910-00-904-9219

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-904-9219

Body Style:
W/mtg bracket, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Diameter:
0.562 inches
Body Length:
1.562 inches
Terminal Diameter:
0.032 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Mounting Facility Type And Quantity:
1 unthreaded mounting holes
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
40.0 megohm-microfarads
Capacitance Value Per Section:
0.470 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
2000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-18312 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-904-9219

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Specification Data:
81349-mil-c-18312/3 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0